

## Philo - Feature #12

### Variable arguments for get\_subpath, and thus, the nodeurl templatetag

08/05/2010 10:05 PM - Joseph Spiros

<b>Status:</b>	Resolved	<b>Start date:</b>	08/05/2010
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Stephen Burrows	<b>% Done:</b>	0%
<b>Category:</b>	Core	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>			
<b>Description</b>			
The semantics of get_subpath on View subclasses should be extended to support variable keyword arguments, and nodeurl should support the new functionality once it exists.			

#### History

##### #1 - 10/20/2010 09:50 PM - Stephen Burrows

- Status changed from New to In Progress

- Assignee set to Stephen Burrows

Reworked node\_url to accept url-tag style args and kwargs in place of a simpler "with <obj>" declaration. Replaced get\_subpath to get\_reverse\_params - it is more flexible and outsources the error handling. If get\_subpath is deemed necessary, it can also make use of the get\_reverse\_params method.

node\_url seems to be working fine as of commit db91ce955e7408382263b8f4ec82915f77d8efb4. Includes unittest.

##### #2 - 10/21/2010 08:05 PM - Stephen Burrows

- Status changed from In Progress to Resolved

Merged into itthinksw/master with commit 9592f8df376c7dacacd49bb7587ee494ad339035.