

Philo - Feature #133

Setting attributes through QuerySetMapper

05/10/2011 01:33 PM - Stephen Burrows

Status:	Resolved	Start date:	05/10/2011
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Core	Estimated time:	0.00 hour
Target version:			
Description			
It would be great to be able to use a call like <code>obj.attributes['hello'] = "Foo"</code> to create an attribute called "hello" with a json value of "Foo". Should theoretically be possible, and would make attributes a lot easier to use.			

Associated revisions

Revision 9cbb247d - 05/10/2011 06:57 PM - Stephen Burrows

Moved efficient QuerySetMappers into `philo.utils` and replaced them with a more complex/differentiated implementation that allows flexibility in terms of caching vs. lazy fetching and tree vs passthrough vs ordinary. Passthrough accepts any number of entities, and all Mappers support *setitem*. (Resolves issue #133.) Added a `set_value` method to Attributes.

History

#1 - 05/10/2011 06:55 PM - Stephen Burrows

This is resolved on the `attribute_access` branch with commit `9cbb247dfb4faa47617438770bb6135155fade16`.

#2 - 05/31/2011 04:04 PM - Stephen Burrows

- Status changed from *New* to *Resolved*

This was merged into the release with commit `7f6fa6595b4c558d7a97ed00cdb19469db4919df`.