

Philo - Feature #25

Add node to request object

10/06/2010 02:58 PM - Stephen Burrows

Status:	Resolved	Start date:	10/06/2010
Priority:	Low	Due date:	
Assignee:	Stephen Burrows	% Done:	0%
Category:	Core	Estimated time:	0.00 hour
Target version:			
Description			
It might be useful to have middleware that provides the current node (if any) as request.node. Occasionally, for example, someone may want to write a view that overrides a certain address but which still references the node at that path.			

History

#1 - 10/06/2010 02:58 PM - Stephen Burrows

- Status changed from New to Feedback

Thoughts?

#2 - 10/07/2010 01:21 AM - Joseph Spiros

Although I'm not immediately aware of a case where I would use this, it seems like something that may be useful to others, or in the future. So, sure. Not even sure if a middleware makes sense, since the request needs to be processed for a node to be found. But then, we could put the node finding into the middleware, make the middleware required, and then use the request.node object in the router view.

#3 - 10/07/2010 04:11 AM - Stephen Burrows

We could also write the router view to use request.node if available and otherwise use the node-finder.

#4 - 10/20/2010 09:53 PM - Stephen Burrows

- Status changed from Feedback to In Progress

- Assignee set to Stephen Burrows

This is currently implemented in my node_middlewares branch. The commit is currently 01a66d144c3ac6539991c5b9f00e1bd5bab132ee, but I may rebase the work onto ithinksw/master if that is desired.

#5 - 10/21/2010 08:05 PM - Stephen Burrows

- Status changed from In Progress to Resolved

Merged into ithinksw/master with commit 9592f8df376c7dacacd49bb7587ee494ad339035